

RING TERMINAL RED 6.4MM0.5-1.5MM 100PCS

Art.no: 16-RV1-6

Red insulated ring terminal. Hole size 6.4 mm, M6. For cable area 0.5-1.5 mm². Pack of 100 pieces.

Technical information

Dimensions (LxHxW)	6,4 mm
Cable area	Red 0,5-1,5 mm ²
Stift/Hylsa/Tätning/Hus /Skarv	Ringkabelsko
Quantity in B-package	100 st
Weight (kg)	0.200000



PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated
 Insulation: Vinyl (PVC)
 Operating temperature: -10-75 °C
 Max. electrical current: 600V
 Max. electrical rating: red 197A, blue 277A, yellow 48A



DIMENSIONS

Wire range	Part nr.	Od2	W	F	L	B	OD	Od1	T	UL
22-16 AWG 0.5-1.5 mm ²	RPVD 1.25-30IN	3.2	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	RPVD 1.25-345IN	3.7	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	RPVD 1.25-40IN	4.3	6.0	17.0	21.0	10.0	4.3	1.7	0.75	
	RPVD 1.25-50IN	5.3	10.0	18.0	23.0	10.0	4.3	1.7	0.75	
	RPVD 1.25-60IN	6.5	11.0	20.0	25.5	10.0	4.3	1.7	0.75	
16-14 AWG 1.5-2.5 mm ²	RPVD 1.25-80IN	8.4	14.0	22.0	29.0	10.0	4.3	1.7	0.75	
	RPVD 1.25-100IN	10.5	18.0	24.0	33.0	10.0	4.3	1.7	0.75	
	RPVD 2.5-30IN	3.2	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	RPVD 2.5-50IN	3.7	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	RPVD 2-40IN	4.3	6.0	17.0	21.0	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm ²	RPVD 2-60IN	6.5	11.0	21.0	26.5	10.0	5.0	2.3	0.8	
	RPVD 2-80IN	8.4	14.0	22.0	29.0	10.0	5.0	2.3	0.8	
	RPVD 2-100IN	10.5	18.0	23.5	32.5	10.0	5.0	2.3	0.8	
	RPVD 2-120IN	13.0	18.0	25.0	34.0	10.0	5.0	2.3	0.8	
	RPVD 5.5-40IN	4.3	6.0	21.0	25.0	13.0	6.7	3.4	1.0	
4-6 mm ²	RPVD 5.5-60IN	6.5	11.0	22.5	28.0	13.0	6.7	3.4	1.0	
	RPVD 5.5-80IN	8.4	14.0	24.0	31.0	13.0	6.7	3.4	1.0	
	RPVD 5.5-100IN	10.5	18.0	26.0	33.0	13.0	6.7	3.4	1.0	
	RPVD 5.5-120IN	13.0	18.0	28.0	37.0	13.0	6.7	3.4	1.0	