

## RING TERMINAL BLUE 6.4MM1.5-2.5MM 100PCS

Art.no: 16-RV2-6

Blue insulated ring terminal. Hole size 6.4 mm, M6. For cable area 1.5-2.5 mm<sup>2</sup>. Pack of 100 pieces.

### Technical information

|                                |                              |
|--------------------------------|------------------------------|
| Dimensions (LxHxW)             | 6,4 mm                       |
| Cable area                     | Blue 1,5-2,5 mm <sup>2</sup> |
| Stift/Hylsa/Tätning/Hus /Skarv | Ringkabelsko                 |
| Quantity in B-package          | 100 st                       |
| Weight (kg)                    | 0.150000                     |



PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated  
 Insulation: Vinyl (PVC)  
 Operating temperature: -10-75 °C  
 Max. electrical current: 600V  
 Max. electrical rating: red 19A  
 blue 27A  
 yellow 48A



DIMENSIONS

| Wire range                           | Part nr.        | Od2  | W    | F    | L    | B    | OD  | Od1 | T    | UL |
|--------------------------------------|-----------------|------|------|------|------|------|-----|-----|------|----|
| 22-16 AWG<br>0.5-1.5 mm <sup>2</sup> | REPO 1.25-30IN  | 3.2  | 6.0  | 16.0 | 19.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 1.25-345IN | 3.7  | 6.0  | 16.0 | 19.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 1.25-40IN  | 4.3  | 6.0  | 17.0 | 21.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 1.25-50IN  | 5.3  | 10.0 | 18.0 | 23.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 1.25-60IN  | 6.5  | 11.0 | 20.0 | 25.5 | 10.0 | 4.3 | 1.7 | 0.75 |    |
| 16-14 AWG<br>1.5-2.5 mm <sup>2</sup> | REPO 1.25-80IN  | 8.4  | 14.0 | 22.0 | 29.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 1.25-100IN | 10.5 | 18.0 | 24.0 | 33.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REPO 2.5-30IN   | 3.2  | 6.0  | 16.0 | 19.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 2.5-50IN   | 3.7  | 6.0  | 16.0 | 19.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 2-40IN     | 4.3  | 6.0  | 17.0 | 21.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
| 12-10 AWG<br>4-6 mm <sup>2</sup>     | REPO 2-60IN     | 6.5  | 11.0 | 21.0 | 26.5 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 2-80IN     | 8.4  | 14.0 | 22.0 | 29.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 2-100IN    | 10.5 | 18.0 | 23.5 | 32.5 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 2-120IN    | 13.0 | 18.0 | 25.0 | 34.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REPO 5.5-40IN   | 4.3  | 6.0  | 21.0 | 25.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
| 4-6 mm <sup>2</sup>                  | REPO 5.5-60IN   | 6.5  | 11.0 | 22.5 | 28.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REPO 5.5-80IN   | 8.4  | 14.0 | 24.0 | 31.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REPO 5.5-100IN  | 10.5 | 18.0 | 26.0 | 33.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REPO 5.5-120IN  | 13.0 | 18.0 | 28.0 | 35.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |